

Technical Data Sheet Roller Blind fabrics for : **Clio mørklæggende**

Article characteristics

 Material Composition 100% PES	 Transparent ☐	 Flame Retardant ☐	 Light Fastness 6
 Width in mm 2000	 Semi-transparent ☐	 Anti Static ☒	 Cutting direction A + B
 Thickness in mm 0.43	 Opaque ☐	 Suitable For Humid Environment ☒	 Pattern Repeat Width cm
 Weight in gr/ m2 320	 Room Darkening ☒	 Anti Bacterial ☐	 Pattern Repeat Height cm

Cleaning

 Hand ☐	 Sponge ☒	 Brush ☐
--	---	---

Assembly

 Laser ☐	 Ultra ☐	 Knife ☒	 Friction ☐
---	---	--	--

Environmental labels

 PVC Free ☒	 Oeko-tex® ☒	 GreenGuard ☒	 Made from recycled plastic waste ☐
 Halogen Free ☒	 Oeko-tex® RCY ☐	 Made with recycled content ☐	 Made from biodegradable waste ☐

Light and energy values

	A	B	D
Glass (mm)	4	4/12/4	4/16/4
U-value [W/(M ² K)]	5.80	2.90	1.10
g-value[-]	0.85	0.76	0.32
G=1/(1/U+1/G2)[W/(M ² K)]	4.86	2.64	1.06



Values according to EN 410 / EN ISO 52022-1 / EN ISO 14501:2020 (%)

EN ISO 14501:2020

Colour	Rv	TV Total	TV Diff	TV Dir	Rs	Ts	Tuv	g	gA	gB	gD	Comfort value (Fc)	Glare control	Opacity Performance
5034	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5132	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5142	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5143	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5144	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5147	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5148	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5149	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5240	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2
5344	82	0	0	0	69	0	0	8	29	36	24	0.58	4	2