

Technical Data Sheet Roller Blind fabrics for : Ester mørklæggende

Article characteristics

Material Composition 100% PES	Transparent ☐	Flame Retardant ☒ B1/M1	Light Fastness 6-7
Width in mm 3000	Semi-transparent ☐	Anti Static ☒	Cutting direction B
Thickness in mm 0.50	Opaque ☐	Suitable For Humid Environment ☒	Pattern Repeat Width cm
Weight in gr/m2 420	Room Darkening ☒	Anti Bacterial ☐	Pattern Repeat Height cm

Cleaning

Hand ☐	Sponge ☒	Brush ☐
----------------------------------	---	-----------------------------------

Assembly

Laser ☐	Ultra ☐	Knife ☒	Friction ☐
-----------------------------------	-----------------------------------	--	--------------------------------------

Environmental labels

PVC free ☒	Oeko-tex® ☒	GreenGuard ☒	Made from recycled plastic waste ☐
Halogen free ☒	Oeko-tex® RCY ☐	Made with recycled content ☐	Made from biodegradable waste ☐

Light and energy values

	A	B	D
Glass (mm)	4	4/12/4	4/16/4
U-value [W/(M²K)]	5.80	2.90	1.10
g-value[-]	0.85	0.76	0.32



Values according to EN 410 / EN ISO 52022-1 / EN ISO 14501:2020 (%)

EN ISO 14501:2020

Colour	Rv	TV Total	TV Diff	TV Dir	Rs	Ts	Tuv	g	gA	gB	gD	Comfort value (Fc)	Glare control	Opacity Performance
5714	84	0			71	0	0	7	28	30	11	0.46	4	4
5715	84	0			71	0	0	7	28	30	11	0.46	4	4
5716	84	0			71	0	0	7	28	30	11	0.46	4	4
5717	84	0			71	0	0	7	28	30	11	0.46	4	4